

ASIO-4060– 4 Channel Relay Output Module

02/17/14



Features	
4 channels relay outputs, (2) Form A (2) Form C	
-10 ~ 70°C Operating Temperature	
Serial interface to SoftPLC using ADAM-4000 TLM	

Specifications			
Relay Output		General	
Channels	(2) Form A (2) Form C	Connectors	(2) plug-in terminal blocks (#14 ~ 22 AWG)
Breakdown Voltage	500 VAC (50/60 Hz)	Power Consumption	0.8 W @ 24 VDC
Contact Rating (Resistive)	0.6 A @ 125 VAC 0.3 A @ 250 VAC 2 A @ 30 VDC 0.6 A @ 110 VDC	Watchdog Timer	System (1.6 second)
Initial Insulation Resistance	1 G Ω min. at 500 VDC	Supported Protocols	ASCII command
Relay Time (Typical)	Off: 2 ms On: 3 ms	Power Input	Unregulated 10 ~ 30 VDC
Maximum Operating Speed	20 operations/min (at related load)	Module Dimensions	110 x 60 x 27 mm (HxWxD)
		Construction Material	Impact Resistant ABS plastic
		Certifications & Compliances	FM, CE, FCC rated, ROHS Compliant

Environment	
Humidity	5 ~ 95% RH
Temperature	Operating: -10 ~ 70°C (-14 ~ 158°F)
	Storage: -25 ~ 85°C (-13 ~ 185°F)