

ASIO-4521– Addressable RS-422/485 to RS-232 Converter

02/06/14



Features
Connects RS-422/485 devices to an RS-232 network
Assigns an address to RS-232 devices for easier network communication
RS-232 and 485 can be set to different baudrates
RS-485 surge protection and automatic RS-485 data flow control
Software configurable to either addressable or non-addressable mode

Specifications

Serial Communications		General	
Input	RS-485 (2-wire) or RS-422 (4-wire)	Connectors	(1) plug-in terminal block (#14 ~ 22 AWG) (RS-422/485) (1) DB9-F (RS-232)
Output	RS-232 (4-wire)	Isolation Voltage	1000 VDC
Speed Modes (bps)	300 600 1,200 2,400 4,800 9,600 19.2 k 38.4 k 57.6 k 115.2 k RS-232/422 mode (switchable)	Power Consumption	1.0 W @ 24 VDC
Built-in microprocessor and watchdog timer			
Power Input	Unregulated 10 ~ 30 VDC w/reversal protection		
LED	Power & Data flow		
Module Dimensions	110 x 60 x 27 mm (HxWxD)		
Construction Material	Impact Resistant ABS plastic		
Certifications & Compliances	UL, UL(C), CE, FCC rated, ROHS Compliant		
Environment			
Temperature	Operating: -10 ~ 70°C (14 ~ 158°F)		
	Storage: -25 ~ 85°C (-13 ~ 185°F)		
Humidity	5 ~ 95% RH		

