

# “Headless” Web Studio HMI

Cat Nos SSH-0x

## Overview

These industrial PC's, with your choice of operating system and SoftPLC Web Studio pre-installed, can be used in applications where a display is not required or paired with our industrial touchscreen monitors (Cat Nos SSM-x) or used with your own monitor.



A separate CPU and monitor rather than a combined PanelPC unit are often a good solution in environments where displays can be easily damaged.

The “Headless” HMI is also a good fit when a remotely mounted, or other special purpose display is desired.

SYSTEM	
CPU	Intel Atom D2550 1.86GHz Dual Core Processor
System Memory	2GB DRAM
Monitor Connections	DVI/D, HDMI
External I/O Ports	2 x USB 2.0 type A, USB4/5 1 x RS-232/422/485 DB-9, COM1 1 x RS-232 DB-9, COM2; 1 x RS-232 internal 2 x GB Ethernet RJ-45 1 x Audio Out 3 pins terminal block connector, DC Power input
Storage	16GB SSD
Expansion Slots	1 x SDHC
Operating System Options	Embedded CE.NET 6.0, Windows7 Pro Embedded, Windows 7 Embedded, WinXP, WinXP embedded
POWER	
Power Consumption	1.4A
Power Input	9~36V DC
MECHANICAL	
Construction	Sliver aluminum chassis
Mounting	Panel or VESA 75 x 75
Dimensions (WxHxD)	200 x 146 x 39mm
Net Weight	2.3 Kgs/ 5.07 Lbs
ENVIRONMENTAL	
Operating Temperature	0~45°C (32 ~ 113°F)
Storage Temperature	-20~60°C (-4 ~ 140°F)
Relative Humidity	10 to 90% @ 40°C, non- condensing
Certificates	CE / FCC Class A, RoHS

25603 Red Brangus Drive, Spicewood, TX 78669

512-264-8390 or 800-SoftPLC (US/Canada)

FAX: 512-264-8399

info@softplc.com



www.softplc.com